

Product datasheet:

Cable glands Progress® AgreenO EMC easyCONNECT nickel-plated brass lead-free with contact spring

Short entry thread metric

Approval type: Progress AgreenO EMV easyCONNECT

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Entry thread Pg and NPT



Article number:	1083.32LF
EAN:	7611614347202
Packaging quantity:	25
Price group:	520

Dimensions / Form

Thread:	M32x1.5
Spanner size:	36 mm
Dimension H:	33 mm
Thread length L:	8 mm

Connections / Entries

Min. clamping range:	21 mm
Max. clamping range:	25.5 mm
Clamping range with inlet min.:	17 mm
Clamping range with inlet max.:	21 mm
clamp technology:	Compression technology
Contact:	Contact spring

Safety / Properties


Lead-free:	Yes
Shielded design (EMC):	Yes

Features

Properties:	For a quick and safe installation of partially dismantled cables as well as thoroughly shielded cables
Thread type:	metric
Thread length:	short

Approvals / Certifications

Protection class:	IP69
Protection class with condition:	IP 68 (10 bar) / IP69



Product datasheet:

VDE: Yes

Storage / Installation / Operation

Minimum operating temperature:	-60 °C
Maximum operating temperature:	100 °C



Assembly instructions



Certificates



Planning data