

Product datasheet:

AGRO combination conduit glands Progress® EMC nickel-plated brass with integrated cable gland

Long entry thread metric

Approval type: Progress MS Kombi EMC

- One-piece sealing insert
- not overall length insulated
- Depending on the type of conduit, the stabilising bush must be ordered separately.
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.



Article number:	1710.80.20.110.4
E-No:	126638562
EAN:	7611614145662
Packaging quantity:	25

Dimensions / Form

Thread:	M20x1.5
Spanner size:	24/29 mm
Dimension H:	38 mm
Thread length L:	10 mm

Connections / Entries

Min. clamping range:	8 mm
Max. clamping range:	11 mm
clamp technology:	Compression technology

Safety / Properties

Shielded design (EMC):	Yes
------------------------	-----

Features


Properties:	Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland
Thread type:	metric
Thread length:	long

Approvals / Certifications

Protection class:	IP68
VDE:	Yes

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	100 °C



Assembly instructions



Planning data