

Product datasheet:

AGRO Adapters Progress® nickel-plated brass with integrated EMC cable gland

Long entry thread metric

Approval type: Progress MS Kombi EMC

- One-piece sealing insert
- not overall length insulated
- 1 = Metric coarse-pitch thread (with VDE Testreport)
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.



Article number: **1165.80.25.160**

E-No: 126648610

EAN: 7611614142258

Packaging quantity: 25

Dimensions / Form

Spanner size:	30 mm
Dimension H:	46 mm
External thread:	M25x1.5
Internal thread:	M25x1.5
Thread length L:	11 mm

Connections / Entries

Min. clamping range:	13 mm
Max. clamping range:	16 mm
clamp technology:	Compression technology

Safety / Properties

Shielded design (EMC):	Yes
------------------------	-----


Features

Properties:	Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland
Thread type:	metric
Thread length:	long
Product type:	Adapter

Approvals / Certifications

Protection class:	IP68
VDE:	Yes

Storage / Installation / Operation



Assembly instructions



Certificates



Planning data

Product datasheet:

Minimum operating temperature:	-40 °C
Maximum operating temperature:	100 °C