

## Product datasheet:

# AGRO Adapters Progress® nickel-plated brass with integrated EMC cable gland

## Long entry thread Pg

### Approval type: Progress MS Kombi EMC

- One-piece sealing insert
- not overall length insulated
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.



**Article number:** **1165.80.29.230**

**EAN:** 7611614142111

**Packaging quantity:** 10

### Dimensions / Form

**Spanner size:** 38/40 mm

**Dimension H:** 48 mm

**External thread:** Pg 29

**Internal thread:** Pg 29

**Thread length L:** 12 mm

### Connections / Entries

**Min. clamping range:** 19 mm

**Max. clamping range:** 23 mm

**clamp technology:** Compression technology

### Safety / Properties

**Shielded design (EMC):** Yes

### Features

**Properties:** Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland

**Thread type:** Pg

**Thread length:** long

**Product type:** Adapter


### Approvals / Certifications

**Protection class:** IP68

### Storage / Installation / Operation

**Minimum operating temperature:** -40 °C

**Maximum operating temperature:** 100 °C



UK  
CA



Assembly instructions



Planning data