

## Product datasheet:

# Synthetic cable glands Syntec® with lamellar technology

## Entry thread Pg

### Approval type: SYNTEC

- Black RAL 9005
- One-piece sealing ring



|                        |                   |
|------------------------|-------------------|
| <b>Article number:</b> | <b>1545.16.14</b> |
| E-No:                  | 121754429         |
| EAN:                   | 7611614078175     |
| Packaging quantity:    | 50                |

### Dimensions / Form

|                  |       |
|------------------|-------|
| Thread:          | Pg 16 |
| Spanner size:    | 27 mm |
| Dimension H:     | 30 mm |
| Thread length L: | 10 mm |

### Connections / Entries

|                      |                    |
|----------------------|--------------------|
| Min. clamping range: | 8.5 mm             |
| Max. clamping range: | 14 mm              |
| Clamping range UL:   | 11.5 - 14 mm       |
| clamp technology:    | Lamella technology |

### Features


|              |                                                                      |
|--------------|----------------------------------------------------------------------|
| Properties:  | halogen-free, black UV resistant (tested according to EN ISO 4892-2) |
| Thread type: | Pg                                                                   |

### Approvals / Certifications

|                   |      |
|-------------------|------|
| Protection class: | IP68 |
|-------------------|------|

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -30 °C |
| Maximum operating temperature: | 100 °C |



Assembly instructions