

## Product datasheet:

# Synthetic straight conduit connector

## Synthetic straight conduit connector

- Quick connector RQG-P
- Black
- Executions with CTG or NPT entry thread



|                        |                     |
|------------------------|---------------------|
| <b>Article number:</b> | <b>5020.026.213</b> |
| E-No:                  | 126683003           |
| EAN:                   | 7611614098685       |
| Packaging quantity:    | 50                  |

### Dimensions / Form

|                      |         |
|----------------------|---------|
| Thread:              | Pg 13   |
| Spanner size:        | 24 mm   |
| Ø B:                 | 26.0 mm |
| Ø I:                 | 13.5 mm |
| Measurement value C: | 13.0 mm |
| Measurement value D: | 43.0 mm |

### Features

|             |                                                                                                                           |
|-------------|---------------------------------------------------------------------------------------------------------------------------|
| Properties: | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
|-------------|---------------------------------------------------------------------------------------------------------------------------|

|              |    |
|--------------|----|
| Thread type: | Pg |
|--------------|----|

### Approvals / Certifications

|                   |            |
|-------------------|------------|
| Protection class: | IP69       |
| Fire class:       | V0 (UL 94) |
| VDE:              | Yes        |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 120 °C |

