

## Product datasheet:

# Synthetic conduit connector with long entry thread

## Synthetic conduit connector

- Connector FLEXAquick RQGKZA
- Black
- Two-piece sealing insert
- 1 = One-piece sealing insert



|                        |                     |
|------------------------|---------------------|
| <b>Article number:</b> | <b>5114.254.250</b> |
| E-No:                  | 126831006           |
| EAN:                   | 7611614489865       |
| Packaging quantity:    | 10                  |

### Dimensions / Form

|                      |          |
|----------------------|----------|
| Thread:              | M50x1.5  |
| Spanner size 1:      | 55 mm    |
| Wrench size 2:       | 65 mm    |
| Dimension B:         | 68.0 mm  |
| Measurement value C: | 14.0 mm  |
| Measurement value D: | 112.0 mm |

### Connections / Entries

|                                 |       |
|---------------------------------|-------|
| Min. clamping range:            | 37 mm |
| Max. clamping range:            | 42 mm |
| Clamping range with inlet min.: | 33 mm |
| Clamping range with inlet max.: | 37 mm |

### Features

|             |                                                                                                                           |
|-------------|---------------------------------------------------------------------------------------------------------------------------|
| Properties: | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
|-------------|---------------------------------------------------------------------------------------------------------------------------|

### Material / Colour

|                |                     |
|----------------|---------------------|
| Material Note: | Nickel-plated brass |
|----------------|---------------------|

### Approvals / Certifications

|                   |            |
|-------------------|------------|
| Protection class: | IP69       |
| Fire class:       | V0 (UL 94) |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 120 °C |

