

## Product datasheet:

# Synthetic straight conduit connector with integrated strain-relief

## Synthetic straight conduit connector with integrated strain-relief

- Quick connector RQGZ-M
- Black



|                        |                     |
|------------------------|---------------------|
| <b>Article number:</b> | <b>5020.031.220</b> |
| E-No:                  | 126676530           |
| EAN:                   | 7611614127026       |
| Packaging quantity:    | 20                  |

### Dimensions / Form

|                      |         |
|----------------------|---------|
| Thread:              | M20x1.5 |
| Spanner size 1:      | 21 mm   |
| Wrench size 2:       | 24 mm   |
| Ø B:                 | 23.0 mm |
| Ø I:                 | 13.0 mm |
| Measurement value C: | 8 mm    |
| Measurement value D: | 59 mm   |

### Connections / Entries

|                      |       |
|----------------------|-------|
| Min. clamping range: | 8 mm  |
| Max. clamping range: | 11 mm |

### Features

|              |                                                                                                                           |
|--------------|---------------------------------------------------------------------------------------------------------------------------|
| Properties:  | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
| Thread type: | metric                                                                                                                    |

### Approvals / Certifications

|                   |            |
|-------------------|------------|
| Protection class: | IP69       |
| Fire class:       | HB (UL 94) |
| VDE:              | Yes        |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 120 °C |

