

## Product datasheet:

# Synthetic conduit connector 90° bend with entry turnable thread nickel-plated brass

## Synthetic conduit connector bend 90°

- Quick connector RQBK90DR-M
- Black
- Executions with Pg entry thread



|                     |               |
|---------------------|---------------|
| Article number:     | 5121.021.220  |
| EAN:                | 7611614205366 |
| Packaging quantity: | 50            |

### Dimensions / Form

|                      |         |
|----------------------|---------|
| Thread:              | M20x1.5 |
| Spanner size:        | 27 mm   |
| Ø B:                 | 29.5 mm |
| Ø I:                 | 13.0 mm |
| Measurement value C: | 12 mm   |
| Measurement value E: | 72 mm   |
| Measurement value F: | 62 mm   |

### Features

|              |                                                                                             |
|--------------|---------------------------------------------------------------------------------------------|
| Properties:  | Quick and pull-out-proof installation by means of the «push-in» lock, outer thread turnable |
| Thread type: | metric                                                                                      |

### Material / Colour

|                |                     |
|----------------|---------------------|
| Material Note: | Nickel-plated brass |
|----------------|---------------------|

### Approvals / Certifications

|                   |            |
|-------------------|------------|
| Protection class: | IP 69      |
| Fire class:       | V2 (UL 94) |
| VDE:              | Yes        |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 120 °C |

