

## Product datasheet:

# Synthetic conduit connector 45° bend

## Synthetic conduit connector 45° bend

- Quick connector RQB45-M
- Black
- Executions with NPT entry thread



|                        |                     |
|------------------------|---------------------|
| <b>Article number:</b> | <b>5100.034.240</b> |
| E-No:                  | 126821800           |
| EAN:                   | 7611614158341       |
| Packaging quantity:    | 10                  |

### Dimensions / Form

|                      |         |
|----------------------|---------|
| Thread:              | M40x1.5 |
| Spanner size:        | 45 mm   |
| Ø B:                 | 44.0 mm |
| Ø I:                 | 29.0 mm |
| Measurement value C: | 14.0 mm |
| Measurement value E: | 73.5 mm |
| Measurement value F: | 77.0 mm |

### Features

|              |                                                                                                                           |
|--------------|---------------------------------------------------------------------------------------------------------------------------|
| Properties:  | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
| Thread type: | metric                                                                                                                    |

### Approvals / Certifications

|                   |            |
|-------------------|------------|
| Protection class: | IP69       |
| Fire class:       | V0 (UL 94) |
| VDE:              | Yes        |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 120 °C |

