

Product datasheet:

Universal Mounting Plate Detection Systems

Mounting plate suitable for the quick, neat and secure installation of various detection systems (such as: fire alarms, smoke detectors, PIR sensors, auxiliary indicators, dome cameras) in suspended (system) ceilings.

Specifications:

- Closed system with integrated strain relief and a dust- and insect-proof finish in accordance with NEN 2535.
- Universally applicable, regardless of the make or type of detection system.
- Simple installation at working height prior to fitting the ceiling panel.
- Includes a marking option for wiring and a connection point for a secondary indicator.
- Suitable for routing one or two (flexible) conduits, with an optional second upper section.

Installation:

Drill a Ø48 mm hole in the ceiling panel. Secure the mounting plate to the top. After installation, fit the base on the visible side, connect the wiring and install the detection system.

Advantages:

- Time savings on site thanks to smart pre-assembly.
- A neat and secure end result with no loose parts.
- Compatible with all standard fire detection and security systems.



Article number: **AT1570**

EAN: 8712259616162

Packaging quantity: 30

Dimensions / Form

Product Ø:	117 mm
Product inner Ø:	78 mm
Product depth:	87 mm
Installation opening (wall/ceiling) Ø:	48 mm
Installation opening (for devices) max. depth:	55 mm

Connections / Entries

For conduit Ø: 19 mm

Assembly / Installation

Room boundary type:	Wooden modular/room cell construction
Installation type:	Classic wiring/assembly
Room delimitation type Design:	hollow ceiling
Device fastening in/on box/housing:	Screw attachment

Safety / Properties

Halogen-free: Yes

Material / Colour

Material: Plastic PP

Product datasheet:

Colour:	grey
---------	------

RAL no.:	7012
----------	------

Approvals / Certifications

Protection class:	IP40
-------------------	------