

(type testing with assurance of conformity by production surveillance)

The products submitted by the applicant was type tested in accordance with the requirements of the mentioned standards. Eurofins certifies the conformity of the product with the standards. Presumption of conformity with the mentioned European directives and Swiss regulations can be assumed. Continuous surveillance based on harmonized European procedures assures the ongoing conformity of the tested products. This certificate has been issued under the presumption and conditional on the fact that the manufacturer fulfils the requirements written in the EU directives and Swiss regulations.

Results of testing are shown in report number: **26CH-00427OR01.S01**

This document is valid until: **2029-08-23**

Eurofins Electric & Electronic Product Testing AG
Swiss Certification Body


Holger Schaffer
Product Certification



Annex to certificate

Eurofins CERTIFEL CoC SEV

Certificate number 26 SEV 10009.01

Additional information

Ersatz für das Zertifikat N°: 16 SEV 0167.01
- Eine Konstruktionsprüfung wurde für die Erweiterung der Gültigkeit des Zertifikates angewendet

Family	Dimensions	Temperature range
Progress MS	M6 – M63	-40 °C ... +100 °C
Progress MS L	M16 – M4	-40 °C ... +100 °C
Progress MS FKN	M8 – M40	-40 °C ... +100 °C
Progress MS FK	M16 – M63	-40 °C ... +100 °C
Progress MS Multi	M16 – M40	-40 °C ... +100 °C
Progress MS T	M16 – M40	-40 °C ... +100 °C
Progress MS W 90	M12 – M40	-40 °C ... +100 °C
Progress MS Adapter	M12 – M63	-40 °C ... +100 °C
Progress MS Kombi	M12 – M63	-40 °C ... +100 °C
Progress MS HT	M6 – M63	-40 °C ... +200 °C
Progress GFK	M8 – M63	-20 °C ... +100 °C
Progress GFK Multi	M16 – M32	-20 °C ... +100 °C
Progress MS KB	M10 – M75	-40 °C ... +100 °C
Progress T+KB	M16 – M40	-40 °C ... +100 °C
Progress S2	M8 – M63	-40 °C ... +100 °C
Progress S2 HT	M6 – M63	-40 °C ... +200 °C
Progress S4 HT	M6 – M63	-40 °C ... +200 °C
Progress MS EMV	M8 – M63	-40 °C ... +100 °C
Progress MS EMV Rapid	M12 – M32	-40 °C ... +100 °C
Progress MS EMV FKN	M8 – M32	-40 °C ... +100 °C
Progress MS Adapter EMV	M10 – M63	-40 °C ... +100 °C
Progress MS Kombi EMV	M12 – M63	-40 °C ... +100 °C
Progress EMV Serie 85	M16 – M63	-40 °C ... +100 °C
Progress EMV easyConnect	M12 – M63	-60 °C ... +100 °C
Progress EMV powerConnect	M16 – M75	-60 °C ... +100 °C
Syntec MS	M12 – M63	-40 °C ... +100 °C
Syntec	M12 – M63	-30 °C ... +100 °C
Serie 51/52	M8 – M25	-40 °C ... +100 °C