Product datasheet:

Splittable Frame LC-Series, size 16

Splittable Frame Series 1921.xx.LC, top-loader

· Set of 4 stainless steel AISI304 fastening screws with black Dacromet finishing



Article number:	**1921.16.LC**
EAN:	7611614523910
Packaging quantity:	10

Dimensions / Form	
Installation opening length:	86 mm
Installation opening width:	36 mm
Dimension A:	120 mm
Dimension B:	58 mm
Measurement value C:	20.3 mm
Borehole distance X:	103 mm
Borehole distance Y:	32 mm

Features	
Properties:	Halogen and silicone free

Approvals / Certifications	
Protection class:	IP54

Storage / Installation / Operation	
Minimum operating temperature:	-40 °C
Maximum operating temperature:	130 °C

The splittable frames of the 1921.xx.LC series are designed for various cable configurations, with or without connectors. They are compatible with small and large grommets from the 1929.SPC and 1929.SPN series and allow for flexible cable entry with variable diameters.

The gasket is pre-mounted on the frame, allowing the frame to be installed directly on the enclosure. The frame is secured with stainless steel screws, while the mounting nuts are overmolded.

· For SPC and SPN grommets
· Fixing screws in steel AISI304
· High pull-out forces according to EN 62444
· Colour black
· overmolded gasket acc. to UL 94 V-0