

Product datasheet:

US50 Junction box for masonry walls Ø 16 mm

Flush-mounted junction boxes & accessories

- Applicable in half stone walls: Diameter box = height stone + joints.
- Equipped with 2 conical pipe inlets at the back of the box, one of which is closed by a break-out gate.
- Tube locking by supplied key.
- Anchoring in mortar by raised edge at the back of the box.
- Halogen-free.



Article number:	⇒ AT1107
EAN:	8712259000442
Packaging quantity:	100


Connections / Entries

Number of entries:	2
For conduit Ø:	16 mm

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method:	Facing brickwork
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	No
Couplable:	No
Equipped with:	
Diameter:	77 mm
Length:	
Width:	
Depth:	
Inner depth:	50 mm
Suitable for wall/board thickness:	
Suitable for number of device inserts:	1
Mounting switching equipment:	Screwing
With screws:	No
Number of non-adjustable device fixing lugs:	
Number of adjustable device fixing lugs:	
Housing feed-through by break-out opening:	No
Housing feed-through by seal membrane:	No



Product datasheet:

Housing feed-through by nozzle:	No
Housing feed-through by step membrane:	No
Suitable for tube diameter:	16 mm
Suitable for cable diameter:	
Pipe locking:	
Pipe locking optional:	No
Inlet from the rear:	No
Number of inlets:	2
Number of included spouts:	0
Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Grey
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Cover model:	Construction protective cover
Transparent cover:	No
Cover attachment:	Snapped on
Sealable:	No
Circuit integrity:	None
With screening:	No
Airtight:	No
Max. conductor cross section:	6 mm ²
Number of poles of the clamp:	0
Clamp position fixed:	No
Luminaire hook mounting:	No
Nozzle:	Tunnel branch pipe
Special application:	None
With partition panel:	
Compliant with BS 4662:	

The complete line of flush-mounted junction boxes offers you the best, fastest installation in every situation. The self-fixating boxes are suitable for installation in materials such as calcium silicate brick, solid gypsum and cellular concrete. For every challenge there is a problem-solving flush-mounted box available from Attema. An advanced selection of parts completes the assortment.