

Product datasheet:

PX Junction box CLASSIC Perilex Ø 19 mm

Flush-mounted junction boxes & accessories

- Suitable for traditional construction.
- Removable abdominal spout.
- Possibility for mounting 2nd belly outlet (art. no. AT4065 to art. no. AT4068).
- Fastening screws M3 x 18 mm.
- Halogen-free.



Article number: **⇒ AT1110**

EAN: 8712259000466

Packaging quantity: 100

Dimensions / Form

Installation opening (wall/ceiling) Ø: 90 mm

Connections / Entries

Number of entries: 1

For conduit Ø: 19 mm

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method: Flush-mounted

Shape: Round

Construction type: Built-in installation box (device box)

Model: Perilex

Provided with revolving ring: No

Couplable: No

Equipped with:

Diameter: 90 mm

Length:

Width:

Depth:

Inner depth: 48 mm

Suitable for wall/board thickness:

Suitable for number of device inserts: 1

Mounting switching equipment: Screwing

With screws: No

Number of non-adjustable device fixing lugs:

Number of adjustable device fixing lugs:

Product datasheet:

Housing feed-through by break-out opening:	No
Housing feed-through by seal membrane:	No
Housing feed-through by nozzle:	No
Housing feed-through by step membrane:	No
Suitable for tube diameter:	19 mm
Suitable for cable diameter:	
Pipe locking:	
Pipe locking optional:	No
Inlet from the rear:	No
Number of inlets:	1
Number of included spouts:	0
Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Grey
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Cover model:	Construction protective cover
Transparent cover:	No
Cover attachment:	Snapped on
Sealable:	No
Circuit integrity:	None
With screening:	No
Airtight:	No
Max. conductor cross section:	6 mm ²
Number of poles of the clamp:	0
Clamp position fixed:	No
Luminaire hook mounting:	No
Nozzle:	Tunnel branch pipe
Special application:	None
With partition panel:	
Compliant with BS 4662:	

The complete line of flush-mounted junction boxes offers you the best, fastest installation in every situation. The self-fixating boxes are suitable for installation in materials such as calcium silicate brick, solid gypsum and cellular concrete. For every challenge there is a problem-solving flush-mounted box available from Attema. An advanced selection of parts completes the assortment.