

Product datasheet:

One-gang box UP¹ with device screws

UP¹ Flush-mounting boxes

- Side-neutral combination
- Many through-wiring possibilities
- With 4 x 3 screw domes
- Standardised combination distance 71 mm

Device box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting device box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic.

Installation opening Ø 60 mm, installation opening Ø 82 mm, depth 46 mm, combination distance 71 mm, protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation,

Entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20/25 mm (2x 20 mm/25 mm in the combination area, 4 x 20 mm/25 mm in the side wall, 1 x 20 mm and 1x up to 11 mm in the box base).

Open through-wiring, fully insulated through-wiring close to the floor, with 4 x 3 screw domes and 2 expanding claw fields, with 2 device screws



Article number:  **1056-05**

EAN: 4013456593985

Inner packing / Packaging quantity: 25 / 450

Price group: 110

Dimensions / Form

Product depth: 46 mm

Connections / Entries

For conduit Ø: 25 mm

Wire entry Ø max.: 11 mm

Assembly / Installation

Assembly type: UP (solid construction)

Safety / Properties

Halogen-free: Yes

Features

Number of screw domes: 4 x 3

Approvals / Certifications

VDE: Yes

UP¹, the new flush-mounted range for electrical installations, takes installation to a whole new level and makes it easier than ever before. The tried-and-tested standard flush-mounted box has been updated and now boasts many new, practical features.

- Side-neutral combination
- Many through-wiring possibilities
- With 4 x 3 screw domes



Assembly instructions



Certificates



Technical information



Planning data

Product datasheet:

· Standardised combination distance 71 mm