

Product datasheet:

Plaster compensation ring Ø 60 mm, height 24 mm

UP¹ plaster levelling compound

- to compensate for deep-seated boxes
- To maintain IP protection class
- With 2 screwed-in device screws
- with 2 ring attachment screws

Plaster compensation ring for flush-mounting/masonry installation, plaster compensation ring for flush-mounted device box according to DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, installation opening Ø 60 mm, depth 24 mm, Protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation, with 2 x 3 screw domes, with 2 device screws



Article number:  **1155-64**

EAN: 4013456594524

Inner packing / Packaging quantity: 25 / 250

Price group: 120

Dimensions / Form

Product depth: 24 mm

Assembly / Installation

Assembly type: UP (solid construction)

Approvals / Certifications

VDE: Yes



Planning data

The well-known plaster levelling rings have been expanded to include triple screw domes for device mounting. These allow devices to be installed flush with the wall and standardised, even in boxes that are mounted too deep.

- To compensate for boxes that are positioned too low
- To maintain IP protection class
- For all UP¹ boxes