

Product datasheet:

Flush-mounting sound insulation one-gang junction box

Flush-mounting sound insulation one-gang junction box

- with 4 screw domes and 2 expanding claw fields
- One-gang junction box for solid construction sound insulation walls
- For conduits up to 25 mm and cables up to Ø 11.5 mm
- Combination distance: 71 mm

Flush-mounting sound insulation box, designed as a one-gang junction box Sound insulation for flush-mounting/masonry installation in sound insulation walls up to 56 dB, Flush-mounting one-gang junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, with sound sheathing, installation opening Ø 60 mm, installation opening Ø 82 mm, depth 60 mm, combination distance 71 mm, protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for soundproof flush-mounting installation, entry markings for NYM cables and DIN EN conduits (6 conduit entries up to 25 mm, 6 wire entries (3 x 1.5 mm², 3 x 2.5 mm² or 5 x 1.5, 5 x 2.5 mm² or 7 x 1.5 mm²), with 4 screw domes and 2 expanding claw fields, without device screws



halogen-free

Article number:	1569-01
EAN:	4013456544505
Inner packing / Packaging quantity:	10 / 100
Price group:	191

Dimensions / Form

Product depth:	60 mm
----------------	-------

Connections / Entries

Number of entries:	6
For conduit Ø:	25 mm

Assembly / Installation

Assembly type:	UP (solid construction)
----------------	-------------------------

Safety / Properties

Sound insulation walls up to:	56
Halogen-free:	Yes
Special application:	sound insulation
Sound insulation:	Yes

Features

Number of screw domes:	4
------------------------	---

Sound insulation box for use in solid construction sound insulation walls with stringent sound insulation requirements. The solid box body with additional sound insulation coating absorbs and reflects the sound, so that interference in adjacent rooms is excluded and the sound insulation remains intact as if no installation box were present.



Assembly instructions



Certificates



Planning data

Product datasheet:

- Maintains the wall's sound insulation protection
- Installation up to 5-unit combinations
- Opposing installation is also possible
- Variable combination connection piece for conduits up to Ø 25 mm
- Flexible for screw and claw fixing of the accessories
- Can be used with sound protection cover as a junction box