Product datasheet:

One-gang junction box UP[1] with device screws



UP[1] Flush-mounting boxes

· Side-neutral combination
· Many through-wiring possibilities
· With 4 x 3 screw domes and 2 expanding claw fields
· Standardised combination distance 71 mm

One-gang junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting device junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic.
Installation opening Ø 60 mm, installation opening Ø 82 mm, depth 66 mm, combination distance 71 mm, protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation,
Entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20/25 mm (2x 20 mm/25 mm and 2x up to 11 mm in the combination area, 8 x 20 mm/25 mm in the side wall, 1 x 20 mm/25 mm and 1x up to 11 mm in the box base).
Open through-wiring, fully insulated through-wiring near the bottom, with 4 x 3 screw domes and 2 expanding claw fields, with 2 device screws

Article number:	**1556-05**
EAN:	4013456594029
Inner packing / Packaging quantity:	25 / 250

Planning data

Dimensions / Form	
Product depth:	66 mm

Connections / Entries	
For conduit Ø:	20 mm, 25 mm
Wire entry Ø max.:	11 mm

Assembly / Installation	
Assembly type:	UP (solid construction)

Safety / Properties	
Halogen-free:	Yes

Features	
Number of screw domes:	4 x 3

Approvals / Certifications	
VDE:	Yes
Environmental Declarations:	SHI-Produktpass 15286-10-1000

UP[1], the new flush-mounted range for electrical installations, takes installation to a whole new level and makes it easier than ever before. The tried-and-tested standard flush-mounted box has been updated and now boasts many new, practical features.

Product datasheet:

· Side-neutral combination
· Many through-wiring possibilities
· With 4 x 3 screw domes and 2 expanding claw fields
· Standardised combination distance 71 mm