

Product datasheet:

One-gang box for nailing, Depth 42 mm

One gang boxes and junction boxes - Basis Installation

- with nail straps as fitting aid
- nail Ø max. 3 mm
- plaster depth min. 6 mm
- dimensions in accordance with German DIN 49073
- for 20 mm conduits

Device box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting device box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic.

Installation opening Ø 60 mm, installation opening Ø 82 mm, depth 42 mm, combination distance 71 mm, protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation, with nail straps,

Entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20 mm (2x 20 mm in both connectors, 4 x 20 mm in the side wall, 1 x 20 mm in the box base), with 2 screw domes and 2 expanding claw fields, without device screws



Article number:	1055-62
EAN:	4013456110908
Packaging quantity:	100
Price group:	120

Dimensions / Form

Product depth:	42 mm
----------------	-------

Connections / Entries

Number of entries:	7
For conduit Ø:	20 mm

Assembly / Installation

Assembly type:	UP (solid construction)
----------------	-------------------------

Safety / Properties

Halogen-free:	Yes
---------------	-----

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Technical information



Planning data