

## Product datasheet:

# One-gang box PERILEX®, Depth 48 mm

## One gang boxes and junction boxes - Basis Installation

- for PERILEX® 16 A inserts
- only for screw fixing
- dimensions in accordance with German DIN 49073
- for 20 mm conduits

Device box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting device box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic.

Installation opening Ø 70 mm, installation opening Ø 82 mm, depth 48 mm, protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation, for PERILEX inserts 16 A

Entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20 mm (6 x 20 mm in the side wall, 2 x 20 mm in the box base), with 2 screw domes, with 2 device screws



Planning data

**Article number:** **1076-04**

EAN: 4013456111806

Inner packing / Packaging quantity: 10 / 100

### Dimensions / Form

Product depth: 48 mm

### Connections / Entries

Number of entries: 8

For conduit Ø: 20 mm

### Assembly / Installation

Assembly type: UP (solid construction)

### Safety / Properties

Halogen-free: Yes