Product datasheet:

Two-gang junction box UP¹

Electronics box UP¹ and Two-gang junction box UP¹



· Side-neutral combination
· Many through-wiring possibilities
· Standardised combination distance 71 mm

two-gang junction box, for Flush-mounting/masonry installation, flush-mounting box, designed as a Flush-mounting two-gang junction box in accordance with DIN EN 60670/ VDE 0606 and DIN 49073, made of plastic.
Installation opening 2x Ø 60 mm, installation opening 152 mm x 82 mm, depth 68 mm, combination distance 71 mm, protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation.
Entries with break-out openings for electric cables and EN conduits with diameters of 20/25 and 25/32 mm (3x 20 mm/25 mm and 3x up to 11 mm in the combination area, 3 x 20 mm/25 mm and 2x 25 mm/32 mm in the side wall, 2 x 20 mm/25 mm and 4x up to 11 mm in the box base),
open through-wiring, fully insulated through-wiring close to the base, with 6 x 3 screw domes, with 4 device screws

Article number:	**1656-05**
EAN:	4013456594289
Inner packing / Packaging quantity:	10 / 100

Planning data

Dimensions / Form

Product width:	80 mm
Product depth:	68 mm
Product length:	149 mm
Drill/cut hole Ø:	2x82 mm

Connections / Entries

For conduit Ø:	20 mm, 25 mm
Wire entry Ø max.:	11 mm

Assembly / Installation

Assembly type:	UP (solid construction)

Safety / Properties

Halogen-free:	Yes

Features

Number of screw domes:	4 x 3

Approvals / Certifications

VDE:	Yes
Environmental Declarations:	SHI-Produktpass 15286-10-1000

Product datasheet:

The electronics box UP[1] and two-gang junction UP[1] box offer generous device installation space and additional installation space for accommodating small switch actuators, for example. The associated separator enables standardised installation of bus and operating voltage in one box.

· Side-neutral combination
· Many through-wiring possibilities
· Standardised combination distance 71 mm