

Product datasheet:

Cavity wall one-gang junction box without support, with device screws, Depth 63 mm

One gang boxes and junction boxes - Basis Installation

- for use in facing masonry
- for combinations: use supports Art. No. 1159-01
- dimensions in accordance with German DIN 49073
- for 20 mm conduits

One-gang junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting one-gang junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic, installation opening Ø 60 mm, installation opening Ø 68 mm, depth 63 mm, without connectors, protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation

Entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20 mm (2x 20 mm in both connectors, 10 x 20 mm in the side wall, 1 x 20 mm in the box base), with 2 screw domes and 2 expanding claw fields, with 2 device screws



Certificates



Technical information



Planning data

Article number:  **1551-00**

EAN: 4013456120303

Inner packing / Packaging quantity: 25 / 250

Price group: 120

Dimensions / Form

Product depth: 63 mm

Connections / Entries

Number of entries: 13

For conduit Ø: 20 mm

Assembly / Installation

Assembly type: UP (solid construction)

Safety / Properties

Halogen-free: Yes

Approvals / Certifications

VDE: Yes