

Product datasheet:

Universal installation housing with mineral fibreboard, 107 x 107 x 72 mm

Universal installation housings

- Two-part, consisting of a housing and a mineral fibreboard cover
- all-round groove indicates the maximum opening size

Universal flush-mounting installation housing, 2-piece, for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting universal installation housing in accordance with DIN EN 60670/VDE 0606, made of plastic with mineral fibreboard.

Base area min. 100 mm x 100 mm, depth min. 50 mm

Opening size max. 77 x 77 mm

Installation depth max. 60 mm

Protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for flush-mounting installation,

entries with break-out openings for electric cables and DIN EN conduits with diameters of 16/20/25 mm (4x 16 mm, 12 x 20 mm, 4x 25 mm and 12x for electric cables in the side wall)



Planning data

Article number:  **1095-22**

EAN: 4013456532168

Packaging quantity: 10

Price group: 120

Dimensions / Form

Product length: 107 mm

Product width: 107 mm

Product depth: 72 mm

Connections / Entries

Number of entries: 32

For conduit Ø: 16 mm

Assembly / Installation

Assembly type: UP (solid construction)

Universal installation housings for a wide range of device installations always ensure optimum installation space for all kinds of devices. The intelligent housing design of all six housings ensures stability and secure hold in the wall.

- For displays, LED lights and much more
- For installing almost all shapes and sizes
- Mineral fibreboard allows individual installation opening