

Product datasheet:

Two-gang junction box with device screws

One gang boxes and junction boxes - Basis Installation

- can also be used as a one-gang junction box (incl. 2 device inserts)
- for use as a junction box cover Art. no. 9062-90 is additionally needed
- use separator wall to separate electrical circuits Art. No. 1656-22 (not illustrated)
- dimensions in accordance with German DIN 49073

Two-gang junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting two-gang junction box in accordance with DIN EN 60670/ VDE 0606 and DIN 49073, made of plastic, installation opening 2x Ø 60 mm, installation opening 152 mm x 70 mm, depth 42 mm, combination distance 71 mm, protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation,

Entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20 mm (2x 20 mm in both connectors, 8 x 20 mm in the side wall, 2 x 20 mm in the box base), with 4 screw domes, with 2 device screws



Article number:	1656-02
EAN:	4013456112605
Inner packing / Packaging quantity:	10 / 100
Price group:	120

Dimensions / Form

Product length:	140 mm
Product width:	60 mm
Product depth:	42 mm

Connections / Entries

Number of entries:	12
For conduit Ø:	20 mm

Assembly / Installation

Assembly type:	UP (solid construction)
----------------	-------------------------

Safety / Properties

Halogen-free:	Yes
---------------	-----

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Planning data