

Product datasheet:

Mini equipment carrier with 4 swivels and 2 ribs

Mini equipment carrier

- Retrofitting in existing composite thermal insulation systems (ETICS)
- consisting of anchor sleeve and attachment core
- for insulation thicknesses of 80 mm and upwards
- Screw-on surface with 10 mm tolerance compensation
- 4 swivel cutters
- 2 ribs
- Sealing lip on all sides
- Weight loading up to 30 N (3 kg)
- equipment attached with self-tapping screws with Ø of 3.2 - 4 mm

Mini equipment carrier
made of plastic
Diameter Diameter 20 mm, depth 60 mm
For retrofitting luminaires, motion detectors, etc. to composite thermal insulation systems (ETICS)
from 80 mm insulation thickness
Attachment surface Diameter 10 mm, tolerance compensation +/- 5 mm, with 4 swivels with clamping ribs and sealing lip
Weight load 30 N (3 kg)

Article number:	 1159-50
EAN:	4013456536197
Inner packing / Packaging quantity:	10 / 100
Price group:	180

Dimensions / Form

Product length:	60 mm
Installation opening (wall/ceiling) length:	Ø20 mm
Installation opening (wall/ceiling) width:	Ø20 mm
Cover for box/housing/casing Ø:	Ø20 mm

Assembly / Installation

Assembly type:	ETICS/external insulation
----------------	---------------------------

Safety / Properties

Halogen-free:	Yes
---------------	-----

Mini equipment carrier for later attachment of a variety of accessories to insulated and already plastered composite thermal insulation systems (ETICS). Luminaires, motion detectors, external sensors etc. can be permanently attached easily, quickly, securely and without creating heat bridges.

- For retrofitting in insulated facades
- Exact flush aligning of attachment devices
- Guarantees installation without heat bridges
- 4 swivels for secure anchoring
- No moisture penetration



Assembly instructions



Certificates



Planning data