

Product datasheet:

In-plaster junction box for flat multi-lead wiring (NYIF), with terminal block, 5 poles

Junction boxes

- for flat multi-lead wiring (NYIF) 1.5 and 2.5 mm²
- terminal block permanently attached
- with plaster disc, cover and cover screw
- Junction box fire-resistant up to 960°C, cover to 850°C in accordance with DIN EN 60670

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic.

Installation opening Ø 70 mm, installation opening Ø 82 mm, depth 16 mm, with plaster disc, cover and cover screw, protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 960°C, cover up to 850°C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation, entries with break-out openings for NYIF 1.5 and 2.5 mm² multi-lead wirings, with 5-pole terminal block



Article number:  **1081-05**

EAN: 4013456130609

Inner packing / Packaging quantity: 25 / 250

Price group: 120

Dimensions / Form

Product depth: 16 mm

Connections / Entries

Number of entries: 7

Assembly / Installation

Assembly type: UP (solid construction)

Safety / Properties

Halogen-free: Yes

Approvals / Certifications

VDE: Yes



Certificates



Planning data