

Product datasheet:

Junction box for KLEMMFIX® mounting, with cover and 2 cover screws

Junction boxes

- KLEMMFIX® mounting possible
- according to German DIN VDE 0606, junction box covers may only be removable using tools
- dimensions in accordance with German DIN 49073
- for 20 mm conduits

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic.

Installation opening Ø 70 mm, installation opening Ø 82 mm, depth 36 mm, with cover, protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for flush-mounting installation, entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20 mm (8 x 20 mm in the side wall), with 2 screw domes



Article number:	1172-92
EAN:	4013456132504
Inner packing / Packaging quantity:	25 / 250
Price group:	120

Dimensions / Form

Product depth:	36 mm
----------------	-------

Connections / Entries

Number of entries:	8
For conduit Ø:	20 mm

Assembly / Installation

Assembly type:	UP (solid construction)
----------------	-------------------------

Safety / Properties

Halogen-free:	Yes
---------------	-----

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Planning data