

Product datasheet:

Extension element for universal equipment carrier

Universal equipment carrier

- to extend the Universal equipment carrier by 100 mm simply by latching on
- can be reduced in 10 mm steps by cutting
- with rock wool pre-cut parts to fill the extension panel

Extension element for universal equipment carriers for mechanically secure and thermal bridge-free installation in insulated exterior walls, extension element, with integrated insulation, thermal bridge-free design in accordance with DIN 18015-5, for installation in insulated exterior walls,

Depth extended by 100 mm, adjustable in 10 mm increments, protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for installation in insulated facades, for 20 mm/25 mm conduits and NYM cables (3 x 1.5 mm², 5 x 1.5 mm² or 3 x 2.5 mm², 5 x 2.5 mm² or 5 x 7.5 mm², low voltage)



Article number:  **1159-27**

EAN: 4013456470613

Packaging quantity: 5

Price group: 180

Dimensions / Form

Product length: 220 mm

Product width: 100 mm

Product depth: 100 mm

Assembly / Installation

Assembly type: ETICS/external insulation

Safety / Properties

Halogen-free: Yes



Assembly instructions



Planning data

Universal equipment carrier for securely attaching electrical installations in or to heat-insulating external facades. Stable attachment of external lights, sockets, motion detectors, external temperature sensors, radio receivers, anemometers, cameras, letter boxes and much more.

- Secure attachment of various equipment to or in insulated external facades.
- Prevents heat bridges
- Quick installation with snap-in connections
- For insulation thicknesses of 60 to 360 mm