

Product datasheet:

Junction box for nailing, Depth 36 mm

Junction boxes

- with nail straps as fitting aid
- nail Ø max. 3 mm
- plaster depth min. 6 mm
- without cover and cover screws
- dimensions in accordance with German DIN 49073
- for 20 mm conduits

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic.

Installation opening Ø 70 mm, installation opening Ø 82 mm, depth 36 mm, protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for flush-mounting installation, with nail straps, entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20 mm (8 x 20 mm in the side wall), with 2 screw domes



Article number: **1172-62**

EAN: 4013456132108

Packaging quantity: 100

Price group: 120

Dimensions / Form

Product depth: 36 mm

Connections / Entries

Number of entries: 8

For conduit Ø: 20 mm

Assembly / Installation

Assembly type: UP (solid construction)

Safety / Properties

Halogen-free: Yes

Approvals / Certifications

VDE: Yes



Certificates



Planning data