

Product datasheet:

Junction box, Depth 56 mm

Junction boxes

- for 8 terminals 1.5 mm², for 6 terminals 2.5 mm² or for 5 terminals 4 mm²
- without cover and cover screws
- For 16 mm / 20 mm conduits

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic.

Installation opening Ø 70 mm, installation opening Ø 82 mm, depth 56 mm, protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for flush-mounting installation, entries with break-out openings for electric cables and DIN EN conduits with a diameter of 20 mm (14 x 20 mm in the side wall), with 2 screw domes



Article number:  **1572-02**

EAN: 4013456132702

Inner packing / Packaging quantity: 10 / 250

Price group: 120

Dimensions / Form

Product depth: 56 mm

Connections / Entries

Number of entries: 14

For conduit Ø: 16 mm

Assembly / Installation

Assembly type: UP (solid construction)

Safety / Properties

Halogen-free: Yes

Approvals / Certifications

VDE: Yes



Certificates



Planning data