

Product datasheet:

Junction casing with cover, 240 x 142 x 87 mm, halogen-free

Junction casings

- suitable for installation of DIN terminal strips, TS 35 standard rails for terminal strips, terminal blocks up to 16 mm², etc.
- including cover

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction casing in accordance with DIN EN 60670/VDE 0606, made of plastic.

Installation opening 240 x 142 mm, installation opening 250 x 150 mm, depth 87 mm, cover with screw fastening, VDE design, has combinability with itself, protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation, entries with break-out openings for electric cables and DIN EN conduits with diameters of 20/25/32 mm (24 x 20 mm, 12 x 25 mm, 6 x 32 mm and 12 x for electric cables in the side wall), with 4 screw domes, with 2 screws



Article number: **1092-90**

EAN: 4013456150003

Packaging quantity: 10

Price group: 120

Dimensions / Form

Product length: 240 mm

Product width: 142 mm

Product depth: 87 mm

Connections / Entries

Number of entries: 58

For conduit Ø: 32 mm

Assembly / Installation

Assembly type: UP (solid construction)

Safety / Properties

Halogen-free: Yes

Approvals / Certifications

VDE: Yes



Certificates



Planning data

Flush-mounting junction casings in all sizes and for almost any kind of jobs. This programme features practical housing sizes as well as robust housing design perfect for building sites.

- As central junction casings for star-shaped cable laying
- Easy to rewire when changing the way rooms are used
- With separator walls to separate electrical circuits
- For installation of DIN terminal strips, TS 35 standard rails for terminal blocks, LSA+ terminal strips and much more
- End cover with screw fastening for VDE-compliant installation