

Product datasheet:

Potential equalisation casing 10² with cover, 107 x 107 x 57 mm

- for bathrooms or similar
- including equipotential bonding busbar, corrosion protected
- including cover

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction casing in accordance with DIN EN 60670/VDE 0606, made of plastic.

Installation opening 100 x 100 mm, installation opening 107 x 107 mm, depth 57 mm, cover with screw fastening, equipotential bonding bar for 6 electric cables up to 10 mm², one electric cable up to 16 mm², protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation, entries with break-out openings for electric cables and DIN EN conduits with diameters of 16/20/25 mm (4x 16 mm, 12 x 20 mm. 4x 25 mm and 12x for electric cables in the side wall), with 4 screw domes, with 2 screws



Article number:  **1095-73**

EAN: 4013456151208

Packaging quantity: 10

Price group: 120



Planning data

Dimensions / Form

Product length: 107 mm

Product width: 107 mm

Product depth: 57 mm

Connections / Entries

Number of entries: 32

For conduit Ø: 25 mm

Assembly / Installation

Assembly type: UP (solid construction)