

Product datasheet:

Potential equalisation casing 16² with cover, 238 x 208 x 68 mm

- for bathrooms or similar
- including equipotential bonding busbar, corrosion protected
- including cover

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction casing in accordance with DIN EN 60670/VDE 0606, made of plastic.

Installation opening 238 x 208 mm, installation opening 250 x 220 mm, depth 68 mm, cover with screw fastening, VDE design, equipotential bonding bar for 7 electric cables up to 16 mm², one circular conductor up to 10 mm thick and one strip up to 30 mm wide, protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for flush-mounting installation, entries with break-out openings for electric cables and DIN EN conduits with diameters of 20/25/32 mm (20 x 20 mm, 8 x 25 mm, 4 x 32 mm in the side wall), with 4 screw domes, with 2 screws



Planning data

Article number: **1097-75**

EAN: 4013456152502

Price group: 120

Dimensions / Form

Product length: 238 mm

Product width: 208 mm

Product depth: 68 mm

Connections / Entries

Number of entries: 32

For conduit Ø: 32 mm

Assembly / Installation

Assembly type: UP (solid construction)

Approvals / Certifications

VDE: Yes