

Product datasheet:

Junction casing with cover, 107 x 107 x 57 mm

Junction casings

- for max. 2 circuits using separator wall
- suitable for installation of DIN terminal strips, TS 35 standard rails for terminal strips, terminal blocks up to 16 mm², etc.
- including cover

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction casing in accordance with DIN EN 60670/VDE 0606, made of plastic.

Installation opening 100 x 100 mm, installation opening 107 x 107 mm, depth 57 mm, cover with screw fastening, VDE design

Protection class IP 20 according to DIN EN 60529, flame retardant according to DIN EN 60695 up to 650° C, for flush-mounting installation, entries with break-out openings for electric cables and EN conduits with diameters of 16/20/25 mm (4x 16 mm, 12 x 20 mm, 4x 25 mm and 12x for electric cables in the side wall), with 4 screw domes, with 2 screws



Article number:	1095-91
EAN:	4013456151406
Packaging quantity:	100
Price group:	120

Dimensions / Form

Product length:	107 mm
Product width:	107 mm
Product depth:	57 mm

Connections / Entries

Number of entries:	32
For conduit Ø:	16 mm

Assembly / Installation

Assembly type:	UP (solid construction)
----------------	-------------------------

Approvals / Certifications

VDE:	Yes
------	-----



Certificates



Planning data

Flush-mounting junction casings in all sizes and for almost any kind of jobs. This programme features practical housing sizes as well as robust housing design perfect for building sites.

- As central junction casings for star-shaped cable laying
- Easy to rewire when changing the way rooms are used
- With separator walls to separate electrical circuits
- For installation of DIN terminal strips, TS 35 standard rails for terminal blocks, LSA+ terminal strips and much more
- End cover with screw fastening for VDE-compliant installation