

Product datasheet:

Junction casing with cover, 159 x 159 x 75 mm, halogen-free

Junction casings

- for max. 2 circuits using separator wall
- suitable for installation of DIN terminal strips, TS 35 standard rails for terminal strips, terminal blocks up to 16 mm², etc.
- including cover

Junction box for flush-mounting/masonry installation, flush-mounting box, designed as a flush-mounting junction casing in accordance with DIN EN 60670/VDE 0606, made of plastic.

Installation opening 165 x 165 mm, installation opening 159 x 159 mm, depth 75 mm, cover with screw fastening, protection class IP 20 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for flush-mounting installation, entries with break-out openings for electric cables and DIN EN conduits with diameters of 20/25/32 mm (16 x 20 mm, 8 x 25 mm, 4 x 32 mm and 12 x for electric cables in the side wall), with 4 screw domes, with 2 screws



Planning data

Article number:	1096-01
EAN:	4013456151505
Packaging quantity:	30
Price group:	120

Dimensions / Form

Product length:	159 mm
Product width:	159 mm
Product depth:	75 mm

Connections / Entries

Number of entries:	40
For conduit Ø:	32 mm

Assembly / Installation

Assembly type:	UP (solid construction)
----------------	-------------------------

Safety / Properties

Halogen-free:	Yes
---------------	-----

Flush-mounting junction casings in all sizes and for almost any kind of jobs. This programme features practical housing sizes as well as robust housing design perfect for building sites.

- As central junction casings for star-shaped cable laying
- Easy to rewire when changing the way rooms are used
- With separator walls to separate electrical circuits
- For installation of DIN terminal strips, TS 35 standard rails for terminal blocks, LSA+ terminal strips and much more
- End cover with screw fastening for VDE-compliant installation