

Product datasheet:

Flush-mounted junction box - 115mm - for flexible corrugated plastic conduits (KRFG)

Flush-mounted junction boxes for flexible corrugated plastic conduits (KRFG)

- Suitable for installation in concrete, masonry and cavity walls
- Easy conduit entries, no conduits in the interior
- 8 x 25 mm conduit entries, more than any other
- Prefix® connection detail to aid fastening to reinforcement bars
- Completely smooth inner surface, no risk of injury
- Optimised cross-shaped projections sealing conduit entry locations - easy to knock out, even when warm
- Optimised tying wire lugs for securing cables



Article number:  **9907.10**

E-No: 155111529

EAN: 7611614263304

Packaging quantity: 20

Dimensions / Form

Product length: 115 mm

Product width: 115 mm

Product depth: 115 mm

Connections / Entries

Number of entries: 22

Assembly / Installation

Assembly type: BB (solid construction)

Safety / Properties

Special application: on-site mixed concrete

Flush-mounted junction boxes with KRFG technology are specially optimised for wiring using KRFG (flexible corrugated plastic) conduits. The specially designed conduit inlets can resist the highest pull-out forces. The conduits can also be secured using rebar ties or cable ties. This enables the electrician to have confidence that the conduits will still be in place after concreting.

- Easy conduit entries, no conduits in the interior
- 8 x 25 mm conduit entries, more than any other
- Easy installation in hollow ceilings and hollow floors
- Prefix® connection detail to aid fastening to reinforcement bars
- Completely smooth inner surface, no risk of injury
- Optimised cross-shaped projections sealing conduit entry locations - easy to knock out, even when warm
- Optimised tying wire lugs for securing cables



Certificates



Planning data