

Product datasheet:

Extension piece - 45mm - for flush-mounted junction box 9907 / 9907.21

Flush-mounted junction boxes for flexible corrugated plastic conduits (KRFG)

- For increasing the front-to-back depth of the box or for sub-ceiling insulation
- Multiple extensions possible
- With two fixing screws



Article number:	9907.68.45
EAN:	7611614240534
Packaging quantity:	5
Price group:	130

Dimensions / Form

Product length:	115 mm
Product width:	115 mm
Product depth:	45 mm

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

Safety / Properties

Special application:	on-site mixed concrete
----------------------	------------------------

Features

Number of screws:	2
-------------------	---

Flush-mounted junction boxes with KRFG technology are specially optimised for wiring using KRFG (flexible corrugated plastic) conduits. The specially designed conduit inlets can resist the highest pull-out forces. The conduits can also be secured using rebar ties or cable ties. This enables the electrician to have confidence that the conduits will still be in place after concreting.

- Easy conduit entries, no conduits in the interior
- 8 x 25 mm conduit entries, more than any other
- Easy installation in hollow ceilings and hollow floors
- Prefix® connection detail to aid fastening to reinforcement bars
- Completely smooth inner surface, no risk of injury
- Optimised cross-shaped projections sealing conduit entry locations - easy to knock out, even when warm
- Optimised tying wire lugs for securing cables



Planning data