

Productgegevensblad:

Ophoogkader 12 mm voor aftakdozen

Flush-mounted junction boxes for flexible corrugated plastic conduits (KRFG)

- voor het vergroten van de diepte van de doos of voor de isolatie onder het plafond
- Meerdere uitbreidingen mogelijk
- met 2 bevestigingsschroeven



Artikelnummer: **9907.68**

EAN: 7611614203690

Verpakkingshoeveelheid: 10

Afmetingen / Vorm

Productlengte: 115 mm

Productbreedte: 115 mm

Productdiepte: 12 mm

Montage / Installatie

Montagetype: BB (massieve constructie)

Veiligheid / Eigenschappen

Speciale toepassing: Stortbeton

Uitrusting

Aantal schroeven: 2



Planningsgegevens

Flush-mounted junction boxes with KRFG technology are specially optimised for wiring using KRFG (flexible corrugated plastic) conduits. The specially designed conduit inlets can resist the highest pull-out forces. The conduits can also be secured using rebar ties or cable ties. This enables the electrician to have confidence that the conduits will still be in place after concreting.

- Easy conduit entries, no conduits in the interior
- 8 x 25 mm conduit entries, more than any other
- Easy installation in hollow ceilings and hollow floors
- Prefix® connection detail to aid fastening to reinforcement bars
- Completely smooth inner surface, no risk of injury
- Optimised cross-shaped projections sealing conduit entry locations - easy to knock out, even when warm
- Optimised tying wire lugs for securing cables