

Productgegevensblad:

Inbouw-aftakdoos 150 mm

Flush-mounted junction boxes for flexible plastic conduits (KRF or KRFG)

- voor hout- en staalbekisting in stortbeton en inbouw in metselwerk
- met binnenliggend deksel als lijmbestevigingsoppervlak
- met verticale bekisting en lijmbesteviging moeten de dozen worden vastgezet met de telescopische steun 9957
- voor losse klemmen tot 4 mm²


concrete construction, junction casing, 115 x 115 x 150 mm, 2-piece

Junction casing for concrete construction installation, on-site mixed concrete, fixing to formwork

Concrete construction box, designed as a concrete construction flush-mounted junction box, made of plastic, for holding clamping materials, for loose terminals up to 4 mm², with internal cover as adhesive attachment surface, with four steel nails and predetermined breaking points for nail removal, with four slotted holes for cover fastening

Length 115 mm, width 115 mm, depth 150 mm

Combination entries with break-out openings for electrical installation conduits (8 x 20/25 mm), break-out openings for electrical installation conduits (16 x 20 mm), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free in accordance with DIN VDE 0604-2-100, for concrete construction installation, on-site mixed concrete



Certificaten



Planningsgegevens

Artikelnummer:	9908.21
EAN:	7611614037752
Verpakkingshoeveelheid:	5

Afmetingen / Vorm

Productlengte:	115 mm
Productbreedte:	115 mm
Productdiepte:	150 mm

Aansluitingen / Invoeringen

Voor buis Ø:	25 mm
--------------	-------

Montage / Installatie

Montagetype:	BB (massieve constructie)
--------------	---------------------------

Veiligheid / Eigenschappen

Speciale toepassing:	Stortbeton
----------------------	------------

Each flush-mounted junction box has a large number of break-out conduit inlets. They are equally suitable for use with flexible plastic conduits of the corrugated (KRFG) or the smooth (KRF) type. The electrician can easily and quickly insert the conduits into the box or pull them through.