

Product datasheet:

Flush-mounted junction box - 115mm - for flexible corrugated plastic conduits (KRFG) with transformer tunnel

Efficient installation and increased reliability thanks to innovative two-part design.

- The conduit entries are secured against accidental opening due to impacts from reinforcement steel or kicks
- Open conduit entries are easily identified during inspections thanks to the junction box's two colours
- Horizontal and vertical slits in the sealing membrane enable the marking cross on the formwork to be seen through the membrane
- Two-part design



Article number:	9907.30
E-No:	155011298
EAN:	7611614482217
Packaging quantity:	5

Dimensions / Form

Product length:	380 mm
Product width:	115 mm
Product depth:	115 mm
Installation opening (for devices) length:	230 mm
Installation opening (for devices) width:	50 mm

Connections / Entries

For conduit Ø:	40 mm
----------------	-------

Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

Safety / Properties

Special application:	on-site mixed concrete
----------------------	------------------------



Certificates



Planning data

Our latest version of this product (Art.-No. 9907.30) also includes an integrated tunnel extension, supporting the trend towards efficient LED strip lighting in residential installations. This product offers all the benefits of the already successful 9907.20 series. The specially designed tunnel extension can accommodate LED strip lighting drivers up to a size of 230 x 50 x 35 mm. Especially in areas such as showers, bathrooms or corridors where LED lighting plays an important role, the flush-mounted junction box with tunnel extension offers an ideal solution. It enables electrical designers to easily incorporate LED strip lighting into their plans, as this item is specially designed for this purpose. It provides flexibility during the installation work on site while helping to ensure safety and reliability.