

## Product datasheet:

# Prefix® 2.0 concrete construction box 1x1

## Prefix® 2.0 concrete construction socket

- Compatible with Feller SNAPFIX®
- For device screws Ø 3 mm
- Max. tightening torque 0.5 Nm



|                        |               |
|------------------------|---------------|
| <b>Article number:</b> | <b>9941</b>   |
| EAN:                   | 7611614334578 |
| Packaging quantity:    | 15            |
| Price group:           | 130           |

### Dimensions / Form

|                |       |
|----------------|-------|
| Product depth: | 90 mm |
|----------------|-------|

### Connections / Entries

|                    |       |
|--------------------|-------|
| Number of entries: | 12    |
| For conduit Ø:     | 32 mm |

### Assembly / Installation

|                |                         |
|----------------|-------------------------|
| Assembly type: | BB (solid construction) |
|----------------|-------------------------|

### Safety / Properties

|                      |                        |
|----------------------|------------------------|
| Special application: | on-site mixed concrete |
|----------------------|------------------------|

Inlet box and wall lamp connection box with Prefix® installation technology, for quick and easy installation against subsequently placed front formwork - without separate supporting element. Thanks to its spring-loaded wing brackets, this one-piece socket with two integrated front parts can be installed in such a way that its front surface will be pressed hard against the front formwork when it is subsequently placed, ensuring the socket will sit just right against the formwork and resulting in a smooth, clean finish after concreting.

- Compatible with Feller SNAPFIX®
- 54% more space
- Extended range includes 1x1, 2x1 NUP, 3x1 NUP
- Extremely robust design
- Pliable projection on the equipment-mounting side to assist locating after plastering
- Spacing projections at end of fixing wings



Planning data