

Productgegevensblad:

Centrale overgangskast voor universele buis invoeren

Box for formwork for universal conduit entries

- materiaal: polypropyleen
- verwerkingstemperatuur: -5 °C/+60 °C

Concrete construction, central transition casing, 326 x 104 x 118 mm, 2-piece
Central transition casing for concrete construction installation, on-site mixed concrete and precast concrete, fixing to formwork and steel formwork
Concrete construction box, designed as a central transition casing for concrete construction, made of plastic, with two slots for system magnets (1299-69 or 1299-70), with an adhesive attachment surface and six steel nails, can be connected in series, front part can be swung out, with ten screw domes for cover fastening
Length 250 mm, width 105 mm, depth 94 mm
Combination entries with break-out openings for electrical installation conduits (24 x 20/25 mm, 6 x 25/32 mm and 2 x 40 mm/50/63), protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for concrete construction installation, on-site mixed concrete and precast concrete



Artikelnummer:	9914.10
EAN:	7611614453767
Verpakkingshoeveelheid:	10

Afmetingen / Vorm

Productlengte:	326 mm
Productbreedte:	104 mm
Productdiepte:	118 mm

Aansluitingen / Invoeringen

Aantal doorvoeren:	36
Voor buis Ø:	63 mm

Montage / Installatie

Montagetype:	BB (massieve constructie)
--------------	---------------------------

Veiligheid / Eigenschappen

Speciale toepassing:	Stortbeton
----------------------	------------



Planningsgegevens

The new box for formwork for concrete structures is primarily used to bring together conduits of different diameters from electrical distribution boards and cable routes. The range of accessories includes plastic screw-down cover and moisture-proof cover made from anodised aluminium. Six metal screws are supplied with both types of cover. The metal screws for the moisture-proof cover are rust-proof. Where insulation material is retrofitted to the underside of a ceiling slab, extension elements can be used to bridge the distance between the concrete slab and the finished ceiling. The advantage of these frames is that they can be combined to accommodate insulation of any thickness. The plastic screw-down cover is designed for neat and secure attachment and for use in dry areas. The moisture-proof cover is suitable for wet rooms.

- Voor de uitlaat van meerdere leidingen, bijv. boven een elektrische verdeler in de lichte wand of opbouw

Productgegevensblad:

- Voor systeemhechtmagneet-, lijm- of spijkerbevestiging
- Buisinvoeren voor Ø 20 mm, Ø 25 mm en Ø 32 mm aan de lange zijden, aan de korte zijden tot Ø 63 mm
- Plaatsing van de buisinvoeren boven de eerste wapeningslaag of de bovenkant van het filigraanplafond