

Product datasheet:

Adapter for bridging through insulation layer | can be installed above the formwork or below the finished ceiling slab

Lamp box with Omega conduit inlets

Article number:	9959.68
E-No:	165920008
EAN:	7611614330907
Packaging quantity:	25

Dimensions / Form

Product Ø:	50 mm
Product length:	150 mm
Installation opening (wall/ceiling) Ø:	50 mm
Drill hole Ø:	50 mm
Drill/cut hole Ø:	50 mm

Assembly / Installation

Min. insulation thickness:	20 mm
Insulation thickness max.:	150 mm
Assembly type:	BB (solid construction)

Safety / Properties

Special application:	on-site mixed concrete
----------------------	------------------------

Features

Number of screws:	2
-------------------	---

Drilling, cutting, crimping, tying - this is the electrician's everyday work. The creation of pipe entries on the building site is as individual as the installer. Agro is an innovative company that has already revolutionised many old ways of doing things in the past. Agro has charted a new course for the industry with the pioneering Omega conduit insertion system. The lamp boxes are type-tested, certified according to EN 60670-1 and 60670-21, and bear the safety mark of the Swiss Federal Inspectorate for Heavy Current Installations (ESTI).

- 7 unique Omega conduit entries 20/25 mm
- Suitable for exposed concrete



Assembly instructions



Certificates



Planning data