

Productgegevensblad:

Verdeeldoos voor plafonds

Ceiling lamp box

- buisvoerbegrenzing om inwendige buisafkorting te vermijden
- Voldoet aan de productnorm EN 60670-21 (ophangbelasting) met onze lamphaken 1225-xx
- max. ophangingsbelasting 50 N (5 kg)

concrete construction, ceiling junction box, 2-part, exit opening Ø 35 mm, depth 99 mm, with light hook slot

Ceiling junction box for concrete construction installation, on-site mixed concrete, fixing to formwork

Concrete construction box, designed as a ceiling junction box in accordance with DIN EN 60670/VDE 0606 and DIN 49073, made of plastic

Installation opening Ø 35 mm, depth 99 mm, integrated conduit retention, with slot for light hooks according to DIN EN 60670 (50N), front part can be swung out, with 4 screw domes, without device screws

Combination entries with impact coupling and conduit entry limit for electrical installation conduits (4 x 20/25 mm) and combination entries with break-out openings for electrical installation conduits (2 x 20/25 mm and 2 x 25/32 mm), Protection class IP 30 according to DIN EN 60529, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for concrete construction installation, on-site mixed concrete



Certificaten



Planningsgegevens

Artikelnummer:	1245-62
EAN:	4013456533196
Verpakking binnenkant / Verpakkingshoeveelheid:	10 / 100

Afmetingen / Vorm

Productdiepte:	99 mm
----------------	-------

Aansluitingen / Invoeringen

Aantal doorvoeren:	8
Voor buis Ø:	25 mm

Montage / Installatie

Montagetype:	BB (massieve constructie)
--------------	---------------------------

Veiligheid / Eigenschappen

Speciale toepassing:	Stortbeton
----------------------	------------

Electric installations with KRFG tubes are one option of dealing with increasing cost pressure. Tube installation is simple, quick and safe.