

Product datasheet:

B¹ Prefix® system wing bracket set

B¹ Prefix® system wings

- Facilitates fixing to the reinforcement
- Pre-fixing by means of B¹ Prefix® installation technology
- Can be used for the following articles:
 - B¹ device socket
 - B¹ device connection socket
 - B¹ large-conduit device connection socket
 - B¹ electronics socket
 - B¹ two-device connection socket
 - B¹ wall light connection socket
 - B¹ universal wall outlet
 - B¹ Prefix® adapter - Ø 20, Ø 25 and Ø 32 mm



concrete construction, Prefix® system wing set, 103 x 49 x 36 mm
 Prefix® system wing set, for concrete construction installation, on-site mixed concrete
 Prefix® system wing set for installation as opposing formwork without support
 elements, made of plastic, for fixing wall boxes or wall-ceiling transitions 30° to the
 reinforcement, for concrete coverings 20 mm to 60 mm, with mounting clips for pre-
 fixing
 Length 103 mm, width 49 mm, depth 36 mm, flame-retardant according to DIN EN
 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for concrete
 construction installation, on-site mixed concrete



Assembly instructions



Planning data

Article number:  **1211-00**

EAN: 4013456551367

Inner packing / Packaging quantity: 1 / 175

Price group: 130

Dimensions / Form

Product length: 103 mm

Product width: 49 mm

Product depth: 36 mm

Assembly / Installation

Minimum concrete cover: 20 mm

Max. concrete cover: 60 mm

Assembly type: BB (solid construction)

Safety / Properties

Special application: on-site mixed concrete

The B¹ Prefix® system wing allows fast, easy fixing to the reinforcement. This means optimal installation on the opposing formwork side and for free-standing reinforcement, and also for sliding or travelling formwork constructions. All wall applications in the new B¹ range have slots for the locking of two Prefix® system wings. This ensures fast, easy installation on the opposing formwork side.

- Fast and easy installation on opposing formwork without support element and abutment
- Holding in place using the Prefix® installation technology leaves both hands free for securing with tie wires
- A pronounced corrugated profile and additional fixing opportunities for secure fixing

Product datasheet:

- using tie wires
- Combinable when using wall and ceiling transitions
- For installation in exposed concrete, pressed against the front formwork
- Suitable for 20 - 60 mm concrete covers