

Product datasheet:

B¹ Prefix® wall outlet adapter

B¹ Prefix® wall outlet adapter

- Facilitates fixing to the reinforcement
- Two slots for B¹ Prefix® system wings
- Can be used for the following articles:
 - End and transition grommet / Article No. 1204-24
 - Wall and ceiling elbow 30° / Article No. 1202-04

Concrete construction, Prefix® wall outlet adapter, Ø 20 mm, 1-piece, with a slot for mounting the Prefix® system wing set

Prefix® adapter for concrete construction installation, on-site mixed concrete
Prefix® adapter for installation on opposing formwork without support elements, made of plastic, for fixing Kaiser Art. no. 1202-04 and Art. no. 1204-24 to the reinforcement with Prefix® system wing set (1211-00)

Length 71.6 mm, width 31 mm, depth 42.2 mm, flame-retardant according to DIN EN 60695 up to 650° C, halogen-free according to DIN VDE 0604-2-100, for concrete construction installation, on-site mixed concrete



Article number:	1211-20
E-No:	155900318
EAN:	4013456551374
Inner packing / Packaging quantity:	25 / 100



Planning data

Connections / Entries

Number of entries:	1
For conduit Ø:	20 mm

Assembly / Installation

Minimum concrete cover:	20 mm
Max. concrete cover:	60 mm
Assembly type:	BB (solid construction)

Safety / Properties

Special application:	on-site mixed concrete
----------------------	------------------------

Using the B¹ Prefix® wall outlet adapter, end and transition grommets, and wall and ceiling 30°-elbows, can be easily and quickly fixed to the reinforcement for pressing against the (not yet placed) front formwork. They have two strong attachment slots, on opposite sides, for clicking the new Prefix® system wing brackets into place.

- Fast and easy installation on opposing formwork without support element and abutment
- For installation in exposed concrete, pressed against the front formwork