

Product datasheet:

KVD50 Kitvast Duo-box Ø 19 mm

Kitvast concrete system junction boxes

- Fitted with adhesive lid.
- Equipped with conical tube inlet with tube snapper.
- Mounting screws: M3 x 18 mm.
- Dimensions of the box is according to 2 coupled MV50 boxes.



Article number:	GD AT4843
EAN:	8712259280493
Packaging quantity:	50

Connections / Entries

Number of entries:	1
For conduit Ø:	19 mm



Assembly / Installation

Assembly type:	BB (solid construction)
----------------	-------------------------

Safety / Properties

Halogen-free:	Yes
Special application:	on-site mixed concrete

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method:	Concrete building
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Double
Provided with revolving ring:	No
Couplable:	No
Equipped with:	
Diameter:	80 mm
Length:	144 mm
Width:	70 mm
Depth:	
Inner depth:	50 mm
Suitable for wall/board thickness:	
Suitable for number of device inserts:	2
Mounting switching equipment:	Screwing
With screws:	No

Product datasheet:

Number of non-adjustable device fixing lugs:

Number of adjustable device fixing lugs:	
Housing feed-through by break-out opening:	No
Housing feed-through by seal membrane:	No
Housing feed-through by nozzle:	No
Housing feed-through by step membrane:	No
Suitable for tube diameter:	19 mm
Suitable for cable diameter:	
Pipe locking:	No
Pipe locking optional:	No
Inlet from the rear:	No
Number of inlets:	1
Number of included spouts:	0
Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Grey
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Cover model:	Construction protective cover
Transparent cover:	No
Cover attachment:	Snapped on
Sealable:	No
Circuit integrity:	None
With screening:	No
Airtight:	No
Max. conductor cross section:	6 mm ²
Number of poles of the clamp:	0
Clamp position fixed:	No
Luminaire hook mounting:	No
Nozzle:	Tunnel branch pipe
Special application:	None
With partition panel:	
Compliant with BS 4662:	

Attema's Kitvast® concrete system is used in cement plants. After measurement, the box and cover are anchored in place with adhesive. After removal of the form, the cover and adhesive are removed from the form. The Kitvast® adhesive covers are designed in such a way that no adhesive residue is visible on the wall. Kitvast® is a flexible system that can be used on all surfaces without causing any damage to the form. Fixing by means of gluing (hot melt). Suitable for steel formwork. Fixing without drilling, i.e. no damage to formwork. Ideal for concrete plants.

Product datasheet:

- Attachment by means of gluing (hot melt).
- Suitable for steel formwork.
- Attachment without drilling, so no damage to formwork.
- Ideal for concrete factories.