

Product datasheet:

Optical termination outlet (OTO), ready to splice with pre-assembled cable, 2x fibres, 25 m

Optical termination outlet (OTO), flush-mounted with pre-assembled cable from the backside

· Scope of delivery: OTO, LC/APC coupling, connector and fibre optic cable

Flush-mounting installation with fibre optic cable for splicing and feed line from the rear
Innovative fibre optic subscriber connection with a maximum installation depth of 32 mm for exact flush-mounting in all standard one-gang junction boxes.

The robust metal support ring with alignment marks allows for convenient installation with screw fastenings.

Perfect fibre storage management thanks to a rotatable and removable storage drum on the rear. Includes holder for up to 4 crimp splice connections.

Equipped with 1x LC/APC quad coupling including shutter and dust cover.

Design compatible with all standard switches



Article number: **⇒ 4250008**

EAN: 4013456579910

Price group: 730

Safety / Properties

Halogen-free: Yes

Features

Network level: 4

Fibre class: Single Mode OS2 (G.657.A2)

Fibre type: Single Mode Optical Fibre

Cable/line length: 25 m

Splice cassette quantity: 1

Number of fibres (max.): 2

Fibre colour coding: 1=red, 2=green

Approvals / Certifications

BauPVo: B2ca according to EN 50575:2014 + A1:2016

Protection class: IP20

Storage / Installation / Operation

Minimum storage temperature: -10 °C

Maximum storage temperature: 60 °C

Minimum installation temperature: -10 °C

Installation temperature max.: 60 °C

Minimum operating temperature: -20 °C

Maximum operating temperature: 60 °C



Assembly instructions



Planning data

Product datasheet:

The optical termination outlet will be the termination point of the optical fibre cable within the appartement / home. Due to the pre-assembled cable in 7 different cable lengths, this variant forms an optimal solution for structured cabling in network level 4.

- Installation in all KAISER one-gang junction boxes
- Ready to splice with pre-assembled cable in 7x lengths (10m, 15m, 20m, 25m, 30m, 50m and 70m) - other lengths available on request
- Available with 2 or 4 fibres
- High-quality fibre-optic cable G.657.A2 and BauPVo B2ca
- Retractable and blowable cable
- Handy Roll-off box with improved installation system
- Compatible with all common TAE design covers