

## Productgegevensblad:

# Compact building distributor, Gf-GV, 4 fibres, CSP, 1 LC/APC QD, IP55

## Compact building distributor (Gf-GV)

· Scope of delivery: Compact Gf-GV, LC/APC QD coupling

Compact building distributor (Gf-GV) can also be used as a house transfer point (HÜP). Suitable for surface mounting. Compact building distributor complies with protection class IP55. Consisting of distributor housing, door, splice cassette and coupling bracket. Suitable for microduct slots, single-pull seals and fibre optic customer cables. 1x slot for microducts and fibre optic cables with a diameter of up to 11.0 mm and 2x outputs for up to 12x patch cables with a diameter of up to 2.0 mm. Equipped with 1x LC/APC quad coupling with dust and laser protection caps. The coupling is installed in the housing and provides access protection for the plug connector. The compact building distributor has a lockable door and can be detached from the housing if necessary. Storage for ANT crimp splice protection and mini heat-shrink tubing. Slot for up to 24x fibre optics and splices distributed across 1x splice cassette. Approved for funding projects by atene KOM



Dimensions: 258 x 186 x 61 mm (LxWxH)

Weight: 1,000 g

Colour: Light grey

Scope of delivery: Compact building distributor including splice cassette,

LC/APC QD coupling

Installation type: Surface-mounted

Protection class: IP55

Number of fibres: 4

Number of splice cassettes: 1

Number of couplings: 1

Coupling type: LC/APC QD

atene KOM approved: Yes

Halogen-free: Yes

Loop length: 250 mm (splice cassette)

Bending radius: 23 mm (splice cassette)

Splice protection holder: ANT crimp / mini heat-shrink tubing

Cable/conduit input quantity: 1

Cable/conduit input Ø: 11.0 mm

Cable/conduit outlet number: 2

Cable/conduit outlet Ø: 12x 2.0 mm

Storage temperature range -10 °C / +60 °C

Installation temperature range -10 °C / +60 °C

Operating temperature range -20 °C / +60 °C

**Artikelnummer:** **⇒ AT29231**

**EAN:** 8712259504735

**Verpakkingshoeveelheid:** 10

### Afmetingen / Vorm

Productlengte: 258 mm

Productbreedte: 186 mm

Productdiepte: 61 mm

### Aansluitingen / Invoeringen

Voor buis Ø: 12 mm

## Productgegevensblad:

### Veiligheid / Eigenschappen

|                        |    |
|------------------------|----|
| Halogeenvrij:          | Ja |
| atene KOM goedgekeurd: | Ja |

### Uitrusting

|                        |   |
|------------------------|---|
| Netniveau:             | 4 |
| Spleißkassette Anzahl: | 1 |
| Aantal vezels:         | 4 |

### Keuringen / Certificeringen

|                                    |                      |
|------------------------------------|----------------------|
| Beschermingsklasse:                | IP55                 |
| Beschermingsklasse met voorwaarde: | IP55 (opbouwmontage) |

### Opslag / Installatie / Gebruik

|                               |        |
|-------------------------------|--------|
| Temperatuur opslag min.:      | -10 °C |
| Temperatuur opslag max.:      | 60 °C  |
| Temperatuur installatie min.: | -10 °C |
| Temperatuur installatie max.: | 60 °C  |
| Gebruikstemperatuur min.:     | -20 °C |
| Gebruikstemperatuur max.:     | 60 °C  |

### ETIM Productklasse: Schakelbord glasvezel

|                                           |             |
|-------------------------------------------|-------------|
| Geschikt voor aantal koppel/chassisdelen: | 6           |
| Geschikt voor aantal module-inzetstukken: |             |
| Met aantal koppelingen/adapters:          | 1           |
| Met frontplaat:                           | Nee         |
| Met behuizing:                            | Nee         |
| Met pigtails:                             | Nee         |
| Type vezel:                               | Overig      |
| Vezelklasse:                              |             |
| APC-uitvoering:                           | Nee         |
| Connectortype buiten:                     | LC-Quad     |
| Connectortype binnen:                     | LC-Quad     |
| Kleur:                                    | Grijs       |
| RAL-nummer:                               | 7.035       |
| Montagewijze:                             | Wandmontage |
| Aantal hoogte-eenheden:                   |             |
| Hoogte:                                   | 258 mm      |
| Breedte:                                  | 186 mm      |
| Diepte:                                   | 61 mm       |

## Productgegevensblad:

The compact building distributor by the the KAISER GROUP is designed for up to 24x fibres and can be delivered in different configuration levels. The compact building distributor can also be used as a house transfer point. Various versions of the compact building distributor have been approved by "atene KOM" and are suitable for use in subsidised projects.

- Protected plug connection, internal fibre optic coupling
- Removable box cover
- Flexibiliteit in FttX concept.
- Gestructureerde FiberManagement.